


# BLUTRON



	Models		
	7K	15K	24K
Function	It reduces chlorine, taste, and odor		
Nominal flow rating	2,2 l/min*	3 l/min*	5 l/min*
Capacity	7.000 l*	15.000 l*	24.000 l*
Nominal filtration rating	0,5 micron		
Working pressure	Min 2 - Max 6 Bar Min 0.2 - Max 0.6 MPa		
Temperature	Min 4 - Max 30 °C Min 40 - Max 86 °F		

	Packaging (6 pcs box)		
	Width	Depth	Height
7K	28 cm	19 cm	22,9 cm
15K	28 cm	20 cm	28 cm
24K	28 cm	20 cm	39,5 cm

Blutron Micro	7K	15K	24K
Diameter Ø	87,4 mm	87,4 mm	87,4 mm
Height (without head)	215 mm	270 mm	385 mm
Height (with head)	245 mm	302 mm	417 mm
Quantity per pallet	672 cartridges	528 cartridges	384 cartridges

Materials	Polypropylene cartridge. Filtration with Blupura carbon block technology with extruded activated carbon. The filter is BPA-free (Bisphenol A), ensuring greater health safety and minimal environmental impact.	Replacement	It is recommended to replace the filter cartridge either at the end of its nominal autonomy or in case of reduced water outlet flow, and in any case within 1 year from installation. To remove the filter cartridge, it is first necessary to close the upstream water inlet and reduce the pressure in the circuit by opening the downstream tap.
Features	Single-use quick-fit cartridge. It reduces the chlorine content, organic compounds and any unpleasant odor and tastes from drinking water, compliant with Italian Ministerial Decrees 174/2004 and 25/2012.	Inactivity	After short periods of inactivity, it is recommended to flush the dispensing system.
Usage	Super microfiltration and drinking water treatment stage. Use not permitted if the water quality has not been determined through analysis or is not microbiologically controlled.	Installation	Either vertically or horizontally. Equipped with a bayonet fitting. When first installed, dispense water for 5 minutes before use.
		Head	Blutron Head or Blutron Head Built-In
		Disposal	EWC 15.02.03 
		Certifications	Check <a href="https://www.blupura.com/en/product/blutron-micro/">https://www.blupura.com/en/product/blutron-micro/</a>

\*Capacities can vary according to the incoming water and nominal flow ratings.

**Cartridge replacement instructions:**

